

Thin Client

Compact Dual Core Series



Compact Dual Core Series is the solution that offers an excellent price-performance ratio

- Wide range of models based on Praim ThinOX, Microsoft CE 6.0R2, Windows XP Embedded SP3, Windows Embedded Standard 7 SP1
- Wide range of applications: from access to centralized infrastructures such as Citrix XenApp, XenDesktop, VMware View, Microsoft RDS, to be used as internet navigation point, or to access IBM iSeries systems
- Powerful 1GHz Dual Core Processor with limited power consumption, less than 11 W
- High reliability and immediate centralized management, thanks to Praim ThinMan management console
- Fanless, silent, efficient and safe
- Native dual monitor DVI support
- 5 external USB ports, 1 in protected slot, built-in speaker
- Options with built-in Wi-Fi and RS232 serial port
- Video resolution up to 1920 x 1440 with a ratio of 4:3 or 16:9 wide screen
- Small and compact can be installed on the back of the LCD monitor

CERTIFIED FOR



OPERATING SYSTEM



Transforming Enterprise Computing

ITALY (HQ)

PRAIM SRL - VIA EZIO MACCANI, 191
38121 TRENTO (TN)
ITALY

p: +39 0461 420517 | f: +39 0461 420581

INFO@PRAIM.COM - WWW.PRAIM.COM

UNITED KINGDOM

PRAIM LTD - LAKESIDE HOUSE, 1 FURZEGROUND WAY
STOCKLEY PARK, UXBRIDGE, UB11 1BD
UNITED KINGDOM

p: +44 (0)20-8622 3031 | f: +44 (0)20-8622 3303

INFO@PRAIM.COM - WWW.PRAIM.CO.UK

Technical specifications	C9010	C9050	C9200	C9100	C9400	C9700	C1000
Processor/ Chipset	VIA Eden X2 1GHz Dual Core / VIA VX900						
Power supply	External 100/240VAC 50/60Hz, 12VDC / 3A max						
Power consumption: active / stand-by	10,9W / 0,7W standard model, 12,9W / 0,7W with built-in wireless option						
Device dim. with stand, weight / Packaging dim., weight	42 (L) x 198 (H) x 140 (P) mm, 0,95Kg / 85 (L) x 303 (H) x 295 (P) mm, 2,0 Kg						
Device marks / Power Supply marks	CE, FCC Class B, Energy Star 5.0 / CE, FCC Class B, GS TUV,UL						
Temperature range / humidity	0° ÷ 35° / 20% ÷ 80%						
Security lock	Kensington						
Display resolution / Colors	DDC 4:3, 16:10 WIDE / up to 1920 x 1440 / 32 bit color						
Operating System	ThinOX	ThinOX	ThinOX	CE 6.0 R2	XPe SP3	WES 7 SP1	PXE Boot
RAM Memory / Flash memory	1GB / 1GB	1GB / 2GB	1GB / 2GB	1GB / 1GB	1GB / 2GB	2GB / 4GB	1GB / 0
Peripherals							
USB ports	6 USB 2.0 ports (2 front + 2 rear + 1 in protected slot + 1 internal (reserved for built-in wireless option))						
LAN Ethernet	10/100/1000 Base T Ethernet RJ45						
Monitor	1 DVI-I port + 1 DVI-D port (with DVI to VGA adapter included)						
PS/2 Mouse and keyboard	1 PS/2 port, PS/2 mouse and keyboard adapter included, optical mouse included						
Serial Port	1 serial port COM1 (DB9 RS-232) optional (alternatively to DVI-D port)						
Parallel port	with adapter from USB to parallel (Option)						
Audio In MIC / Audio Out Headphones	1 x 1/8 inch jack / 1 x 1/8 inch jack						
Built-in wireless 802.11b/g or 802.11b/g/n	Factory option						
Built-in speaker	Built-in speaker 1 W						
Protocols and resident clients							
TCP/IP, DNS, DHCP, FTP, SNMP MIB II	•	•	•	•	•	•	-
Auth. 802.1X Ethernet EAP/PEAP MSCHAPV2	•	•	•		•	•	-
Cisco VPN Client	•	•	•		•	•	-
RDP client	7.0	7.0	7.0	6.00	7.0	7.1	-
VMware View 5.1 client	RDP/PCoIP	RDP/PCoIP	RDP/PCoIP		RDP/PCoIP		-
Citrix ICA / PN Agent / Receiver	ICA 12	ICA 12	ICA 12	ICA 11	Receiver 3.0	Receiver 3.1	-
Virtual Bridges VERDE 6.6		SPICE	SPICE		•	•	-
Client Ericom PowerTerm WebConnect					•	•	-
Leostream / Provision Networks VAS client					•	•	-
Browser		Firefox 11	Firefox 11	IE 6 CE 6.0	IE 7.0	IE 8.0	-
Praim TN5250E/3270 Video/Printer Emulator		•	•	•			-
Praim VT/ASCII Emulator		•	•	•			-
Local PDF Viewer		Acrobat 7	Acrobat 7		Acrobat 7	•	-
Microsoft .NET Framework					2.0	2.0-3.0-3.5	-
Media Player, Wordpad				•	•	•	-
E-mail client		Thunderbird 2.0	Thunderbird 2.0		Outlook Exp.		-
JVM		SUN 1.6	SUN 1.6		•	•	-
Flash Player	Adobe 11	Adobe 11	Adobe 11		•	•	-
Skype voip local client		•	•		•	•	-
NX NoMachine Client		•	•		•	•	-
X11 native Client		•	•		•	•	-
VNC Client		•	•	•	•	•	-
Shell script sessions		•	•				-
CUPS printing support	•	•	•				-
LPD/LPR and RAW	•	•	•	•	•	•	-
User disk partition		50MB	50MB		~ 1GB	~ 1.5GB	-
Praim USB re-direction support	□	□	□		□	□	-
Supported Operating Systems							
Citrix Metaframe 1.7, 1.8, XP, PS 4, 4.5	•	•	•	•	•	•	-
Citrix XenApp 6.0, Citrix XenDesktop 5.0	•	•	•	•	•	•	-
MS Windows 2000/2003/2008 TS	•	•	•	•	•	•	-
Unix/Linux/AIX, NX NoMachine Server		•	•		•	•	-
IBM AS/400, IBM S/390		•	•		•	•	-
Administration / User interface							
Remote management via Praim ThinMan	Freeware	Freeware	Freeware	Freeware	Freeware	Freeware	-
SW Upgrade / VNC shadow / WakeOn LAN	•	•	•	•	•	•	-
Screen saver with password	•	•	•	•	•	•	-
User interface with Desktop and local application toolbar	•	•	•	•	•	•	-
User interface Zero Client VDI mode (Without local desktop)	•	•	•	•	•	•	-
Support multiple concurrent connections	1 Single	•	•	•	•	•	-
Factory Options							
Factory options can be ordered at the same time of the products, using the part numbers provided by the product catalogue							
1 serial port COM1 (DB9 RS-232) - Alternatively to the DVI-D port	•	•	•	•	•	•	•
Built-in wireless 802.11b/g	•	•	•	•	•	•	•
Built-in wireless 802.11b/g/n	•	•	•		•	•	•
Flash disk expansion					4GB	8GB	
DDR3 RAM memory expansion	2GB - 4GB	2GB - 4GB	2GB - 4GB		2GB - 4GB	4GB	2GB - 4GB
Options							
USB to Parallel cable adapter	80EC00012	80EC00012	80EC00012	80EC00012	80EC00012	80EC00012	
105 keys standard USB PC keyboard (Black)	89T110001	89T110001	89T110001	89T110001	89T110001	89T110001	
105 keys PS/2 PC/5250 keyboard	89T110002	89T110002	89T110002	89T110002	89T110002	89T110002	
Add-on Praim Media streaming codecs (76AC00006)	76AC00006	76AC00006	76AC00006				
LCD VESA mounting bracket	80EC00028	80EC00028	80EC00028	80EC00028	80EC00028	80EC00028	80EC00028
External USB 802.11-b/g WiFi dongle	80AC00031	80AC00031	80AC00031	80AC00031	80AC00031	80AC00031	80AC00031
Dual monitor adapter cable from DVI-I to VGA/DVI	80EC00037	80EC00037	80EC00037	80EC00037	80EC00037	80EC00037	80EC00037
Warranty							
1 year ex-factory. Free 2 year warranty extension when the product is registered on the Praim web site							

Note: • Available ◊ Installable from the user based on available free disk space □ Requires ThinMan Enterprise Edition and TCe VDA

All names and trademarks contained in this document, are property of their respective owners. The information in this document is property of Praim SRL.

