



Thin Client

Ino Series



Small, fast, environmentally friendly low power thin client

Ino9000 series is designed to offer high performances accessing Microsoft, Citrix, VMware View and IBM iSeries enterprise servers

- Ideal as **Virtual Desktop Infrastructure** workstation, integrates support towards Citrix XenDesktop and VMware View
- **Very low power consumption**, is a Green solution, only 9W
- **High reliability and easy remote management** provide a lower Total Cost of Ownership (TCO) than a traditional PC or laptop
- **Simple and secure access** to company applications, without the risk of Virus infection
- Enhanced **IBM AS/400 Display and Printer emulation**
- **Very small size**, only 15.6 x 12.2 x 3.6 cm, it can be directly installed on the back of an LCD using the optional VESA connector
- **WiFi support**, with built-in option and external antenna, allows you to offer a small-sized wireless workstation
- **Display resolution up to 1920 x 1440** with 4:3 and 16:9 wide screen support

CERTIFIED FOR



OPERATING SYSTEM



Transforming Enterprise Computing

ITALY (HQ)

UNITED KINGDOM

PRAIM SRL - VIA EZIO MACCANI, 191
38121 TRENTO (TN)
ITALY

PRAIM LTD - LAKESIDE HOUSE, 1 FURZEGROUND WAY
STOCKLEY PARK, UXBRIDGE, UB11 1BD
UNITED KINGDOM

p: +39 0461 420517 | f: +39 0461 420581

p: +44 (0)20-8622 3031 | f: +44 (0)20-8622 3303

INFO@PRAIM.COM - WWW.PRAIM.COM

INFO@PRAIM.COM - WWW.PRAIM.CO.UK

Technical specifications	XT9000-I	XT9200-I	XP9400-I	WE9700-I	PX1000-I
P/N	80X9001I02	80X9201I02	80W9401I02	80W9700I02	80P1001I02
Processor / Chipset	VIA Eden ULV 1000MHz / VIA VX855				
Power supply	external 100/240VAC 50/60Hz, 12V 3A - 36W				
Power consumption: on / stand-by	9W / 1.4W standard version, 11W / 1.4W with built-in wireless				
Device dim, weight / Packaging dim, weight	15,6(H) x 12,2(P) x 3,6(L) cm, 0,680 Kg / 21,6(H) x 23,5(P) x 8,3(L) cm, 1,450 Kg				
Device certifications / Power supply certifications	CE, FCC Class B, UL, Energy Star 5.0 / CE, FCC Class B, GS TUV,UL				
Temperature range / humidity	0° ÷ 35° / 20% ÷ 80%				
Security lock	kensington				
Operating System	ThinOX V8	ThinOX V8	XPe SP3	WES7 SP1	PXE BOOT
RAM Memory / Flash Memory	1GB / 2GB	1GB / 2GB	1GB / 2GB	2GB / 4GB	1GB / -
Display resolution with DDC, 4:3, 16:10 WIDE ratio	1920 x 1440	1920 x 1440	1920 x 1440	1920 x 1440	1920 x 1440
Colors	from 256 to 16,8 Millions				
Peripherals					
USB ports / LAN Ethernet	4 ports USB 2.0 (2 fronts + 2 rear) / 10/100/1000BaseT Ethernet RJ45				
Monitor	1 DVI-I port (Dual Monitor) with DVI-VGA included				
Mouse / PS2 Keyboard	1 x PS2 keyboard (with PS2 mouse + keyboard adapter), optical mouse included				
Parallel connection	With optional USB to parallel adapter				
Audio In MIC / Audio Out Headphone	1 x 1/8 inch jack / 1 x 1/8 inch jack				
Built-in speaker	Built-in 1W speaker				
802.11b/g/n built in wireless	Factory option				
Protocols and resident clients					
TCP/IP, DNS, DHCP, FTP, SNMP MIB II	•	•	•	•	--
802.1X Ethernet EAP/PEAP MSCHAPV2 Authentication	•	•	•	•	--
VPN Client Cisco	•	•	◊	◊	--
Client RDP	7.0	7.0	7.0	7.1	--
Client VMware View 5.1	RDP/PCoIP	RDP/PCoIP	RDP/PCoIP	RDP/PCoIP	--
Citrix ICA / PN Agent / Receiver	ICA 12	ICA 12	Receiver 3.0	Receiver 3.1	--
Virtual Bridges VERDE 6.6		SPICE	◊	◊	--
Ericom PowerTerm WebConnect Client		•	•	•	--
Leostream Client / Provision Networks VAS Client	•	•	◊	◊	--
Browser	Firefox 11	Firefox 11	IE 7.0	IE 8.0	--
Praim TN5250E / 3270 Video e Printer Emulator		•	Opz. Net2000	Opz. Net2000	--
Praim VT/ASCII emulator		•			--
PDF Viewer		Acrobat 7	Acrobat 7	◊	--
Microsoft .NET Framework			2.0	2.0-3.0-3.5	--
Media Player, Wordpad			•	•	--
E-mail client		Thunderbird 2.0	Outlook Exp.		--
JVM		SUN 1.6	◊	◊	--
Flash Player	Adobe 11	Adobe 11	◊	◊	--
Open Office (only up to ThinOX V8.03.xx)		OpenOffice 3.3			--
Client voip Skype locale		•	◊	◊	--
NX Nomachine Client	•	•	◊	◊	--
X11 Client	•	•	•	•	--
Propalms TSE Client	•	•	◊	◊	--
VNC Client	•	•	◊	◊	--
Shell script session	•	•	•	•	--
CUPS printing	•	•	•	•	--
LPD/LPR and RAW	•	•	•	•	--
User Disk Partition		50MB	~ 1GB	~ 1.5GB	--
Praim USB re-direction	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	--
Supported Operating Systems					
Citrix Metaframe 1.7, 1.8, XP, PS Server 4, 4.5	•	•	•	•	--
Citrix XenApp 6.0, Citrix XenDesktop 3.x, 4.0, 5.0	•	•	•	•	--
Microsoft Windows 2000/2003/2008 Terminal Server	•	•	•	•	--
Unix/Linux/AIX, NX NoMachine Server	•	•			--
IBM AS/400, IBM S/390		•	Opt. Net2000	Opt. Net2000	--
Administration					
Remote management via ThinMan	Freeware	Freeware	Freeware	Freeware	--
Upgrade FW /VNC shadow / WakeOn LAN	•	•	•	•	--
Screen saver with password	•	•	•	•	--
Options					
	P/N	P/N	P/N	P/N	P/N
External USB WiFi USB 802.11b/g dongle	80AC00031	80AC00031	80AC00031	80AC00031	80AC00031
Built-in wireless 802.11b/g	80AC00060	80AC00060	80AC00060	80AC00060	80AC00060
Built-in wireless 802.11b/g/n	80AC00063	80AC00063	80AC00063	80AC00063	80AC00063
Factory Flash disk expansion	-	-	-	-	-
Factory Ram DDR2 expansion	1GB/2GB	1GB/2GB	2GB	-	2GB
USB to Parallel cable	80EC00012	80EC00012	80EC00012	80EC00012	80EC00012
105 keys PS/2 keyboard with PC standard layout	80T110001	80T110001	80T110001	89T110001	89T110001
105 keys PS/2 keyboard with PC/5250 double layout	89T110002	89T110002	89T110002	89T110002	89T110002
LCD Monitor VESA Bracket	80EC00017	80EC00017	80EC00017	80EC00027	80EC00027
Praim MediaStream codecs Add-On software license	76AC00006	76AC00006	-	-	-

Warranty					
1 year ex-factory. Free 2 year warranty extension when the product is registered on the Praim web site					
Note:	• Available	◊ Installable from the user based on available free disk space	<input type="checkbox"/>	Requires ThinMan Enterprise Edition	

All names and trademarks contained in this document, are property of their respective owners. The information in this document is property of Praim SRL.

Ver. 1.33

