



Thin Client

Ino SoC Series



Ino Soc Series, the smallest System-on-Chip Thin Client with TI DM8148 processor

Optimized for Citrix HDX protocols and Microsoft Remote FX, is the ideal thin client to access virtual desktop infrastructures with high multimedia performance

- Built-in support to Citrix XenApp, XenDesktop, VMware View, Microsoft RDS with Remote FX infrastructures
- Is a green solution with very low power consumption, only 8W
- Its High reliability and easy remote management through Praim ThinMan console, ensure lower Total Costs of Ownership than a traditional PC
- Simple and secure access to company applications, without the risk of virus infection
- Very small dimensions, including DVI and VGA with dual monitor support, 4 USB external ports
- Video resolution up to 1920 x 1200 @ 30 fps with 3D graphics acceleration
- LCD VESA mounting on the back of the monitor





CERTIFIED FOR






OPERATING SYSTEM







UNITED KINGDOM



| Technical specifications | I9010 |
|--|--|
| Processor/ Chipset | Texas Instruments TM DM8148 1GHZ ARM |
| Power supply | External 100/240VAC 50/60Hz, 12VDC / 2A max |
| Power consumption: active / stand-by | 8,7W / 0,3W |
| Device dim. with stand, weight / Packaging dim., weight | 29 (L) x 145 (H) x 133 (P) mm, 0,6Kg / 83 (L) x 232 (H) x 205 (P) mm, 1,5 Kg |
| Device marks / Power Supply marks | CE, FCC Class B, Energy Star 5.0 / CE, FCC Class B, GS TUV,UL |
| Temperature range / humidity | 0° ÷ 35° / 20% ÷ 80% |
| Security lock | Kensington |
| Operating System | Praim ThinOX |
| RAM memory / Flash memory | 1GB/2GB |
| Dispaly resolution / Colors | DDC 4:3, 16:10 WIDE, 1920 x 1200 Dual Monitor / 32 bit color |
| Peripherals | |
| USB ports | 4 USB 2.0 ports (2 front + 2 rear) |
| LAN Ethernet | 10/100/1000 BaseT Ethernet RJ45 |
| Monitor | 1 DVI-I port + 1 DVI-D port with DVI to VGA adapter included |
| Parallel port | with adapter from USB to parallel (Option) |
| Audio In MIC / Audio Out Headphones | 1 x 1/8 inch jack / 1 x 1/8 inch jack |
| 802.11b/g/ built in wireless | With factory option External USB |
| Built-in speaker | Built-in speaker 1 W |
| USB mouse | Included |
| Protocols and resident clients | |
| TCP/IP, DNS, DHCP, FTP, SNMP MIB II | • |
| Auth. 802.1X Ethernet EAP/PEAP MSCHAPV2 | • |
| Cisco VPN Client | • |
| Client RDP | 7.0 / Remote FX |
| Client VMware View 5.1 | RDP/PCoIP |
| Citrix ICA / Receiver | ICA 12.1 |
| Flash Player | Adobe 11 |
| CUPS printing support | • |
| LPD/LPR e RAW | • |
| Supported Operating Systems | |
| Citrix XenApp 6.0, Citrix XenDesktop 5.6 | • |
| MS Windows 2000/2003/2008 TS / RDS | • |
| VMware View 5.5 | • |
| Administration / User interface | |
| Remote management via Praim ThinMan | Freeware |
| SW Upgrade / VNC shadow / WakeOn LAN | • |
| Screen saver with password | • |
| User interface Zero Client VDI mode (Without local desktop) | • |
| Options | Codice |
| USB to Parallel cable adapter | 80EC00012 |
| 105 keys standard USB PC keyboard (Black) | 89T110009 |
| 105 keys standard USB PC keyboard (Black) with Smart Card Reader | 89T110008 |
| Add-on Praim Media streaming codecs | 76AC00006 |
| LCD VESA mounting bracket | TBD |
| External USB 802.11-b/g WiFi dongle | 80AC00031 |
| Warranty | |
| 1 year ex-factory. Free 2 year warranty extension when the product is registered on the Praim web site | |
| | |

 $\textbf{Warranty: 1} \ \ \text{year ex-factory. Free 2} \ \ \text{year warranty extension when the product is registered on the Praim web site}$

All names and trademarks contained in this document, are property of their respective owners. The information in this document is property of Praim SRL.

Ver. 1.00

